



THIS SPECIFICATION IS THE PROPERTY OF BOE HF AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF BOE HF AND MUST BE RETURNED TO BOE HF UPON ITS REQUEST

SPEC. NUMBER S8-64-8A	PRODUCT GROUP TFT-LCD	Rev. P0	ISSUE DATE 2019.5.6	PAGE 1 OF 35
--------------------------	--------------------------	------------	------------------------	-----------------

NT140WHM-N14

Product Specification Rev. P0

www.szguangzhuo.com
Tel / 信 Wechat : +86-13411884959

BEIJING BOE DISPLAY TECHNOLOGY

www.szguangzhuo.com 广卓液晶屏 echodeng61@hotmail.com jimei@jimeihk.com +86-13411884959

BOE

PRODUCT GROUP

REV

ISSUE DATE

TFT- LCD PRODUCT

P0

2019.5.6

SPEC. NUMBER

SPEC. TITLE

PAGE

S8-64-8A

NT140WHM-N14 Product Specification

3 OF 35


Contents

No.	Items	Page
1.0	General Description	4
2.0	Absolute Maximum ratings	6
3.0	Electrical specifications.	7
4.0	Optical specifications.	9
5.0	Interface Connection	14
6.0	Signal Timing Specification	18
7.0	Signal Timing waveforms	20
8.0	Input Signals, Display Colors & Gray Scale of Colors	22
9.0	Power Sequence	23
10.0	Connector description	24
11.0	Mechanical Characteristics	25
12.0	Reliability Test	26
13.0	Handling & Cautions	26
14.0	Label	27
15.0	Packing information	29
16.0	Mechanical Outline Dimension	30
17.0	EDID Table	32

1.0 GENERAL DESCRIPTION

1.1 Introduction

HB140WX1-100 is a color active matrix TFT LCD module using amorphous silicon TFTs (Thin Film Transistors) as an active switching devices. This module has a 14.0 inch diagonally measured active area with WXGA resolutions (1366 horizontal by 768 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical Stripe and this module can display 262,144 colors. The TFT-LCD panel used for this module is a low reflection and higher color type. Therefore, this module is suitable for Notebook PC. The LED Driver for back-light driving is built in this model. All input signals are LVDS interface compatible.



1.2 Features

- 1 Channel LVDS interface with 1 pixel / clock
- Thin and light weight
- 6-bit color depth, display 262K colors
- Single LED Lighting Bar. (Top side/Horizontal Direction)
- Data enable signal mode
- Side Mounting Frame
- Green Product (RoHS & Halogen free product)
- On board LED Driving circuit
- Low driving voltage and low power consumption
- On board EDID chip

SPEC. NUMBER

SPEC. TITLE

PAGE

S8-64-8A

NT140WHM-N14 Product Specification

5 OF 35

1.3 Application

- Notebook PC (Wide type)

1.4 General Specification

The followings are general specifications at the model HB140WX1-100 (listed in Table 1.)

<Table 1. General Specifications>

Parameter	Specification	Unit	Remarks
Active area	309.4(H) × 173.95(V)	mm	
Number of pixels	1366 (H) × 768 (V)	pixels	
Pixel pitch	0.2265(H) × 0.2265 (V)	mm	
Pixel arrangement	RGB Vertical stripe		
Display colors	262K	colors	
Display mode	Normally White		
Dimensional outline	323.5 (H) × 192 (V) × 5.2 (D:max)	mm	
Weight	350 (max)	g	
Surface treatment	Glare (Clear Black) / Hard coating 3H		
Back-light	Upper edge side, 1-LED Lighting Bar type		Note 1
Power consumption	P_D : 0.95 (max)	W	Note 2
	P_{BL} : 2.9 (max)	W	
	P_{total} : 3.85 (max)	W	

Notes : 1. LED Lighting Bar (40*LED Array)

Notes: 2. Maximum Measurement Condition :R/G/B Pattern


2.0 ABSOLUTE MAXIMUM RATINGS

The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.

< Table 2. Absolute Maximum Ratings > $T_a = -25 \sim +2^\circ\text{C}$

Parameter	Symbol	Min.	Max.	Unit	Remarks
Power Supply Voltage	V_{DD}	-0.3	1.0	V	Note 1
Logic Supply Voltage	V_{IN}	$V_{SS}-0.3$	$V_{DD}+0.3$	V	
Operating Temperature	T_{OP}	0	+50	$^\circ\text{C}$	Note 2
Storage Temperature	T_{ST}	-20	+60	$^\circ\text{C}$	

- Notes : 1. Permanent damage to the device may occur if maximum values are exceeded functional operation should be restricted to the condition described under normal operating conditions.
2. Temperature and relative humidity range are shown in the figure below.
 95 % RH Max. ($40^\circ\text{C} \geq T_a$)
 Maximum wet - bulb temperature at 39°C or less. ($T_a > 40^\circ\text{C}$) No condensation.



3.0 ELECTRICAL SPECIFICATIONS

3.1 Electrical Specifications

< Table 3. Electrical specifications >

Ta=25+/-2°C

Parameter		Min.	Typ.	Max.	Unit	Remarks
Power Supply Voltage	V _{DD}	3.0	3.3	3.6	V	Note 1
Permissible Input Ripple Voltage	V _{RF}	-10%VDD	-	-10%VDD	mV	Note 3
Power Supply Current	I _{DD}	-	-	287	mA	Note 1
Positive-going Input Threshold Voltage	V _{IT+}	-	-	100	mV	V _{cm} = 1.2V typ.
Negative-going Input Threshold Voltage	V _{IT-}	-100	-	-	mV	
Differential Input Voltage	V _{id}	200	-	600	mV	
Power Consumption	P _D	-	-	0.95	W	Note 1
	P _{BL}	-	-	2.90	W	Note 2
	P _{total}	-	-	3.85	W	

Notes :

1. The supply voltage is measured and specified at the interface connector of LCM.

The current draw and power consumption specified is for 3.3V at 25 ° C.

a) Typ : Mosaic pattern 8*8


b) Max : R/G/B patterns



(a)



(b)



Inrush Measure Condition

2. Calculated value for reference (VLED × ILED)

3. Measure condition

4. Input voltage range:3.0~3.6V.Test condition: Oscilloscope bandwidth 20MHz, AC coupling.

3.0 ELECTRICAL SPECIFICATIONS

3.2 Backlight Unit

< Table 4. LED Driving guideline specifications > Ta=25+/-1°C

Parameter		Min.	Typ.	Max.	Unit	Remarks	
LED Forward Voltage		V_F	3.0	3.2	3.4	V	-
LED Forward Current		I_F	-	19	-	mA	-
LED Power Consumption		P_{LED}	-	-	2.9	W	Note 1
LED Life-Time		N/A	15,000	-	-	Hour	$I_F = 20mA$
Power supply voltage for LED Driver		V_{LED}	6	12	21	V	
EN Control Level	Backlight on		2.5		5.0	V	
	Backlight off				0.8	V	
PWM Control Level	PWM High Level		2.5		5.0	V	
	PWM Low Level		0		0.8	V	
PWM Control Frequency		F_{PWM}	180	-	10,000	Hz	
Duty Ratio		-	5	-	100	%	

Notes : 1. Power supply voltage 12V for LED Driver, Driver efficiency 90%,

Calculator Value for reference $I_F \times V_F \times 40 / 0.9 = P_{LED}$

2. The LED Life-time define as the estimated time to 50% degradation of initial luminous.

4.0 OPTICAL SPECIFICATION

4.1 Overview

The test of Optical specifications shall be measured in a dark room (ambient luminance ≤ 1 lux and temperature = $25 \pm 2^\circ\text{C}$) with the equipment of Luminance meter system (Goniometer system and TOPCON BM-5) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of θ and Φ equal to 0° . We refer to $\theta = 0^\circ$ ($= \theta_3$) as the 3 o'clock direction (the "right"), $\theta = 90^\circ$ ($= \theta_{12}$) as the 12 o'clock direction ("upward"), $\theta = 180^\circ$ ($= \theta_9$) as the 9 o'clock direction ("left") and $\theta = 270^\circ$ ($= \theta_6$) as the 6 o'clock direction ("bottom"). While scanning θ and/or Φ , the center of the measuring spot on the Display surface shall stay fixed. The backlight should be operating for 30 minutes prior to measurement. VDD shall be $3.3 \pm 0.3\text{V}$ at 25°C . Optimum viewing angle direction is 6 o'clock.

4.2 Optical Specifications

<Table 5. Optical Specifications>

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Viewing Angle range	Horizontal	θ_3	CR > 10	40	45	-	Deg.	Note 1
		θ_9		40	45	-	Deg.	
	Vertical	θ_{12}		15	20	-	Deg.	
		θ_6		30	40	-	Deg.	
Luminance Contrast ratio		CR	$\theta = 0^\circ$	500	600			Note 2
Luminance of White	5 Points	Y_w	$\theta = 0^\circ$ $I_{LED} = 19\text{mA}$	180	200	-	cd/m ²	Note 3
White Luminance uniformity	5 Points	ΔY_5		80	-	-		Note 4
	13 Points	ΔY_{13}		65	-	-		
White Chromaticity		x_w	$\theta = 0^\circ$	0.283	0.313	0.343		Note 5
		y_w		0.299	0.329	0.359		
Reproduction of color	Red	x_R	$\theta = 0^\circ$	-0.03	0.581	+0.03		
		y_R			0.359			
	Green	x_G			0.335			
		y_G			0.578			
	Blue	x_B			0.154			
		y_B			0.100			
Response Time (Rising + Falling)		T_{RT}	$T_a = 25^\circ\text{C}$ $\theta = 0^\circ$	-	8	16	ms	Note 6
Cross Talk		CT	$\theta = 0^\circ$	-	-	2.0	%	Note 7

Notes :

1. Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing angles are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface (see FIGURE 1).

2. Contrast measurements shall be made at viewing angle of $\theta = 0$ and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state .

(see FIGURE 1) Luminance Contrast Ratio (CR) is defined mathematically.

$$CR = \frac{\text{Luminance when displaying a white raster}}{\text{Luminance when displaying a black raster}}$$

3. Center Luminance of white is defined as luminance values of 5 point average across the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display.

4. The White luminance uniformity on LCD surface is then expressed as : $\Delta Y = \text{Minimum Luminance of 5(or 13) points} / \text{Maximum Luminance of 5(or 13) points}$.

(see FIGURE 2 and FIGURE 3).

5. The color chromaticity coordinates specified in Table 5 shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.


6. The electro optical response time measurements shall be made as FIGURE 4 by switching the "data" input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is T_r , and 90% to 10% is T_d .

7. Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (YA) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (YB) of that same area when any adjacent area is driven dark.

(See FIGURE 5).


4.3 Optical measurements

Figure 1. Measurement Set Up




Optical characteristics measurement setup

Figure 2. White Luminance and Uniformity Measurement Locations (5 points)




Center Luminance of white is defined as luminance values of center 5 points across the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display.

Figure 3. Uniformity Measurement Locations (13 points)




The White luminance uniformity on LCD surface is then expressed as : $\Delta Y5 = \text{Minimum Luminance of five points} / \text{Maximum Luminance of five points}$ (see FIGURE 2) , $\Delta Y13 = \text{Minimum Luminance of 13 points} / \text{Maximum Luminance of 13 points}$ (see FIGURE 3).

Figure 4 Response Time Testing



The electro-optical response time measurements shall be made as shown in FIGURE 4 by switching the “data” input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is T_d and 90% to 10% is T_r .

Figure 5. Cross Modulation Test Description



$$\text{Cross-Talk (\%)} = \left| \frac{Y_B - Y_A}{Y_A} \right| \times 100$$

Where:

Y_A = Initial luminance of measured area (cd/m²)

Y_B = Subsequent luminance of measured area (cd/m²)

The location measured will be exactly the same in both patterns

Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (Y_A) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (Y_B) of that same area when any adjacent area is driven dark (Refer to FIGURE 5).

5.0 INTERFACE CONNECTION.

5.1 Electrical Interface Connection

The electronics interface connector is I-PEX 20455-040E-12 or Compatible or equivalent. The mating connector part number is I-PEX 20455-040T-11 or Compatible. The connector interface pin assignments are listed in Table 6.

<Table 6. Pin Assignments for the Interface Connector>

Terminal	Symbol	Functions
Pin No.	Symbol	Description
1	NC	No Connection
2	VDDIN	Power Supply, 3.3V (typ)
3	VDDIN	Power Supply, 3.3V (typ)
4	VDC	VDC 3.3V power for LED
5	NC	No Connection
6	CLK EDID	EDID Clock
7	Data EDID	EDID Data
8	RxIN0-	Transmission Data of 0 Negative -
9	RxIN0+	Transmission Data of 0 Positive +
10	GND	Ground
11	RxIN1-	Transmission Data of 1 Negative -
12	RxIN1+	Transmission Data of 1 Positive +
13	GND	Ground
14	RxIN2-	Transmission Data of 2 Negative -
15	RxIN2+	Transmission Data of 2 Positive +
16	GND	Ground
17	RxCLKIN-	Sampling Clock of Negative -
18	RxCLKIN+	Sampling Clock of Positive +
19	NC	No Connection
20	NC	No Connection
21	NC	No Connection
22	GND	Ground
23	NC	No Connection
24	NC	No Connection
25	GND	Ground
26	NC	No Connection
27	NC	No Connection
28	GND	Ground
29	NC	No Connection
30	NC	No Connection

BOE

www.szguangzhuo.com 广卓液晶屏 echodeng61@hotmail.com jimei@jimeihk.com +86-13411884959

PRODUCT GROUP

REV

ISSUE DATE

TFT- LCD PRODUCT

P0

2019.5.6


SPEC. NUMBER
S8-64-8A

SPEC. TITLE
NT140WHM-N14 Product Specification

PAGE
15 OF 35


Terminal	Symbol	Functions
Pin No.	Symbol	Description
31	VLED_GND	LED Ground
32	VLED_GND	LED Ground
33	VLED_GND	LED Ground
34	NC	No Connection
35	PWM	System PWM Signal Input
36	LED_EN	LED enable pin(+3.3V Input)
37	NC	No Connection
38	VLED	LED Power Supply 6V-21V
39	VLED	LED Power Supply 6V-21V
40	VLED	LED Power Supply 6V-21V

5-2. LVDS Interface



Note. Transmitter : Thine THC63LVDM63A or equivalent.
Transmitter is not contained in Module.


5.3. LVDS Input signal



Note. Pin connection in case of using Thine THC63LVDM63A

5.3 Data Input Format

<Table 6. Pin Assignments for the Interface Connector>



5.4 Back-light & LCM Interface Connection

Interface Connector: PF040-509B-C09 or Equivalent

<Table 7. Pin Assignments for the BLU & LCM Connector>

Pin No.	Symbol	Description	Pin No.	Symbol	Description
1	LED1	LED cathode connection	6	NC	No Connection
2	LED2	LED cathode connection	7	Vout	LED anode connection
3	LED3	LED cathode connection	8	Vout	LED anode connection
4	LED4	LED cathode connection	9	Vout	LED anode connection
5	NC	No Connection			

6.0 SIGNAL TIMING SPECIFICATION

6.1 The HB140WX1-100 is operated by the DE only.


Item		Symbols	Min	Typ	Max	Unit
Clock	Frequency	1/Tc	67.5	72.3	78.2	MHz
	High Time	Tch	-	47	-	tc
	Low Time	Tcl	-	37	-	Tc
Frame Period		Tv	773	790	812	lines
			-	60	-	Hz
			-	167	-	ms
Vertical Display Period		Tvd	-	768	-	lines
One line Scanning Period		Th	1440	1526	1625	clocks
Horizontal Display Period		Thd	-	1366	-	clocks

6.2 LVDS Rx Interface Timing Parameter

The specification of the LVDS Rx interface timing parameter is shown in Table 8.

<Table 8. LVDS Rx Interface Timing Specification>


Item	Symbol	Min	Typ	Max	Unit	Remark
CLKIN Period	tRCIP	-	13.83	25	nsec	
CLK Difference	tCdiff	-tRCIP*(3/7)	0	+tRCIP*(3/7)	nsec	
Input Data 0	tRIP1	-0.4	0.0	+0.4	nsec	
Input Data 1	tRIP0	tRIP/7-0.4	tRIP/7	tRIP/7+0.4	nsec	
Input Data 2	tRIP6	2 × tRIP/7-0.4	2 × tRIP/7	2 × tRIP/7+0.4	nsec	
Input Data 3	tRIP5	3 × tRIP/7-0.4	3 × tRIP/7	3 × tRIP/7+0.4	nsec	
Input Data 4	tRIP4	4 × tRIP/7-0.4	4 × tRIP/7	4 × tRIP/7+0.4	nsec	
Input Data 5	tRIP3	5 × tRIP/7-0.4	5 × tRIP/7	5 × tRIP/7+0.4	nsec	
Input Data 6	tRIP2	6 × tRIP/7-0.4	6 × tRIP/7	6 × tRIP/7+0.4	nsec	



* Vdiff = (RXO/Ez+)-(RXO/Ez-),.....,(RXO/ECLK+)-(RXO/ECLK-)


7.0 SIGNAL TIMING WAVEFORMS OF INTERFACE SIGNAL

7.1 Sync Timing Waveforms



- 1) Need over 3 H-sync during V-Sync Low
- 2) Fix H-Sync width from V-Sync falling edge to first rising edge

7.2 Vertical Timing Waveforms





SPEC. NUMBER
S8-64-8A

SPEC. TITLE
NT140WHM-N14 Product Specification

PAGE
21 OF 35

7.3 Horizontal Timing Waveforms




8.0 INPUT SIGNALS, BASIC DISPLAY COLORS & GRAY SCALE OF COLORS

	Colors & Gray scale	Data signal																	
		R0	R1	R2	R3	R4	R5	G0	G1	G2	G3	G4	G5	B0	B1	B2	B3	B4	B5
Basic colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
	Light Blue	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Purple	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0
White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	
Gray scale of Red	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	△	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	Darker	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	△																		
	▽																		
	Brighter	1	0	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	
	▽	0	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	
Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0		
Gray scale of Green	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	△	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	Darker	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	
	△																		
	▽																		
	Brighter	0	0	0	0	0	0	1	0	1	1	1	0	0	0	0	0	0	
	▽	0	0	0	0	0	0	0	1	1	1	1	0	0	0	0	0	0	
Green	0	0	0	0	0	0	1	1	1	1	1	0	0	0	0	0	0		
Gray scale of Blue	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	△	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	
	△																		
	▽																		
	Brighter	0	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1	
	▽	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	
Blue	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1		
Gray scale of White	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
	△	1	0	0	0	0	0	1	0	0	0	0	1	0	0	0	0	0	
	Darker	0	1	0	0	0	0	0	1	0	0	0	0	1	0	0	0	0	
	△																		
	▽																		
	Brighter	1	0	1	1	1	1	1	0	1	1	1	1	0	1	1	1	1	
	▽	0	1	1	1	1	1	0	1	1	1	1	0	1	1	1	1	1	
White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1		

9.0 POWER SEQUENCE

To prevent a latch-up or DC operation of the LCD module, the power on/off sequence shall be as shown in below



- $T1 \leq 10 \text{ ms}$
- $0 \text{ ms} \leq T2 \leq 50 \text{ ms}$
- $200 \text{ ms} \leq T3$
- $10 \text{ ms} \leq T4$
- $10 \text{ ms} \leq T5$
- $0 \text{ ms} \leq T6$
- $10 \text{ ms} \leq T7$
- $200 \text{ ms} \leq T8$
- $0 \text{ ms} \leq T9 \leq 50 \text{ ms}$
- $1 \text{ s} \leq T10$

Notes:

- When the power supply VDD is 0V, keep the level of input signals on the low or keep high impedance.
- Do not keep the interface signal high impedance when power is on. Back Light must be turn on after power for logic and interface signal are valid.

10.0 Connector Description

Physical interface is described as for the connector on LCM.

These connectors are capable of accommodating the following signals and will be following components.

10.1 TFT LCD Module

Connector Name /Description	For Signal Connector
Manufacturer	IPEX or Compatible
Type/ Part Number	I-PEX 20455-040E-12 or Compatible
Mating housing/ Part Number	I-PEX 20455-040T-11 or Compatible

SPEC. NUMBER

SPEC. TITLE

PAGE

S8-64-8A

NT140WHM-N14 Product Specification

25 OF 35

11.0 MECHANICAL CHARACTERISTICS

11.1 Dimensional Requirements

FIGURE 6 shows mechanical outlines for the model HB140WX1-100.
Other parameters are shown in Table 9.

<Table 9. Dimensional Parameters>

Parameter	Specification	Unit
Active Area	309.40 (H) × 173.35 (V)	
Number of pixels	1366 (H) X 768 (V) (1 pixel = R + G + B dots)	
Pixel pitch	0.2265 (H) X 0.2265 (V)	
Pixel arrangement	RGB Vertical stripe	
Display colors	262K	
Display mode	Normally white	
Dimensional outline	323.5*192.5.2 (max)	mm
Weight	350 (max)	gram
Back Light	Connector : PF040-B09B-C09	
	LED, Horizontal-LED Array type	

10.2 Mounting

See FIGURE 6.

10.3 Glare and Polarizer Hardness.

The surface of the LCD has an glare coating to maximize readability and hard coating to reduce scratching.

10.4 Light Leakage

There shall not be visible light from the back-lighting system around the edges of the screen as seen from a distance 50cm from the screen with an overhead light level of 350lux.

12.0 RELIABILITY TEST

The Reliability test items and its conditions are shown in below.

<Table 10. Reliability test>

No	Test Items	Conditions
1	High temperature storage test	Ta = 60 °C , 240 hrs
2	Low temperature storage test	Ta = -20 °C , 240 hrs
3	High temperature & high humidity operation test	Ta = 50 °C , 80%RH, 240 hrs
4	High temperature operation test	Ta = 50 °C , 240 hrs
5	Low temperature operation test	Ta = 0 °C , 240 hrs
6	Thermal shock	Ta = -20 °C ↔ 60 °C (0.5 hr), 100 cycle
7	Vibration test (non-operating)	1.5G, 10~500Hz, Half Sine X, Y, Z / Sweep rate : 1 hour
8	Electro-static discharge test (non-operating)	Air : 150 pF, 330Ω, 15 KV Contact : 150 pF, 330Ω, 8 KV

13.0 HANDLING & CAUTIONS

- (1) Cautions when taking out the module
 - Pick the pouch only, when taking out module from a shipping package.
- (2) Cautions for handling the module
 - As the electrostatic discharges may break the LCD module, handle the LCD module with care. Peel a protection sheet off from the LCD panel surface as slowly as possible.
 - As the LCD panel and back - light element are made from fragile glass material, impulse and pressure to the LCD module should be avoided.
 - As the surface of the polarizer is very soft and easily scratched, use a soft dry cloth without chemicals for cleaning.
 - Do not pull the interface connector in or out while the LCD module is operating.
 - Put the module display side down on a flat horizontal plane.
 - Handle connectors and cables with care.
- (3) Cautions for the operation
 - When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the LCD panel would be damaged.
 - Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.

BOE

PRODUCT GROUP

REV

ISSUE DATE

TFT- LCD PRODUCT

P0

2019.5.6

SPEC. NUMBER

SPEC. TITLE

PAGE

S8-64-8A

NT140WHM-N14 Product Specification

27 OF 35

(4) Cautions for the atmosphere

- Dew drop atmosphere should be avoided.
- Do not store and/or operate the LCD module in a high temperature and/or humidity atmosphere. Storage in an electro-conductive polymer packing pouch and under relatively low temperature atmosphere is recommended.

(5) Cautions for the module characteristics

- Do not apply fixed pattern data signal to the LCD module at product aging.
- Applying fixed pattern for a long time may cause image sticking.

(6) Other cautions

- Do not disassemble and/or re-assemble LCD module.
- Do not re-adjust variable resistor or switch etc.
- When returning the module for repair or etc., Please pack the module not to be broken. We recommend to use the original shipping packages.

14.0 LABEL

(1) Product label



1 2 3 4 5 6 7

X	X	X	X	X	X	1	0	0	X	X	X	X	X	X	X
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

Type designation

No 5. Month (1, 2, 3, ..., 9, X, Y, Z)

No 1. Control Number

No 6. Product Identification (FG)

No 2. Rank / Grade

No 7. Serial Number

No 3. Line classification

No 4. Year (10: 2010, 11: 2011, ...)

TFT- LCD PRODUCT

P0


2019.5.6

SPEC. NUMBER
S8-64-8A

SPEC. TITLE
NT140WHM-N14 Product Specification

PAGE
28 OF 35

(2) High voltage caution label

	HIGH VOLTAGE CAUTION	COLD CATHODE FLUORESCENT LAMP IN LCD PANEL CONTAINS A SMALL AMOUNT OF MERCURY. PLEASE FOLLOW LOCAL ORDINANCES OR REGULATIONS FOR DISPOSAL.
	RISK OF ELECTRIC SHOCK. DISCONNECT THE ELECTRIC POWER BEFORE SERVICING	

(3) Box label

Label Size: 110 mm (L) × 56 mm (W)

Contents

Model: HB140WX1-100

Q`ty: Module Q`ty in one box

Serial No.: Box Serial No. See next figure for detail description.

Date: Packing Date

Internal use of Product




00	0	0	00	0	0000	000000
Type	Grade	Line	Year	Month	Internal use	Serial No


15.0 PACKING INFORMATION

15.1 Packing order


– Put Pad into the inner box



– Put module into the paper spacer and modules bundled by PE Bag



– Put Cover on the top of the pad and Sealing the box



– 12 inner box / Pallet


Pallet Packing by stretch film

15.2 Notes

- Box Dimension: 526mm(W) x 346mm(D) x 448mm(H)
- Package Quantity in one Box: 38pcs
- Total Weight: 16kg

16.0 MECHANICAL OUTLINE DIMENSION

Figure 6. TFT-LCD Module Outline Dimension (Front View)



17.0 EDID Table

Address (HEX)	Function	Hex	Dec	crc	Input values.	Notes
00	Header	00	0	-	0	EDID Header
01		FF	255	-	255	
02		FF	255	-	255	
03		FF	255	-	255	
04		FF	255	-	255	
05		FF	255	-	255	
06		FF	255	-	255	
07		00	0	-	0	
08	ID Manufacturer Name	09	9	-	BOE	ID = BOE
09		E5	229	-		
0A	ID Product Code	85	133	-	131	ID = 2181
0B		08	8	-		
0C	32-bit serial No.	00	0	-	-	
0D		00	0	-	-	
0E		00	0	-	-	
0F		00	0	-	-	
10	Week of manufacture	1	1	-	1	
11	Year of Manufacture	1D	29	-	2019	Manufactured in 2019
12	EDID Structure Ver.	01	1	-	1	EDID Ver 1.0
13	EDID revision #	04	4	-	4	EDID Rev. 0.4
14	Video input definition	95	149	-	-	Refer to right table
15	Max H image size	1F	31	-	31	31 cm (Approx)
16	Max V image size	11	17	-	17	17 cm (Approx)
17	Display Gamma	78	120	-	2.2	Gamma curve = 2.2
18	Feature support	02	2	-	-	RGB display, Preferred Timing mode
19	Red/Green low bits	BF	191	-	-	Red / Green Low Bits
1A	Blue/White low bits	60	96	-	-	Blue / White Low Bits
1B	Red x high bits	94	148	594	0.581	Red (x) = 10011110 (0.581)
1C	Red y high bits	5C	92	367	0.359	Red (y) = 01011001 (0.359)
1D	Green x high bits	55	85	343	0.335	Green (x) = 01010101 (0.335)
1E	Green y high bits	94	148	591	0.578	Green (y) = 10011100 (0.578)
1F	Blue x high bits	27	39	157	0.154	Blue (x) = 00100110 (0.154)
20	BLue y high bits	19	25	102	0.100	Blue (y) = 00011010 (0.100)
21	White x high bits	50	80	320	0.313	White (x) = 01010000 (0.313)
22	White y high bits	54	84	336	0.329	White (y) = 01010100 (0.329)

BOE

PRODUCT GROUP

REV

ISSUE DATE

TFT- LCD PRODUCT

P0

2019.5.6

SPEC. NUMBER

SPEC. TITLE

PAGE

S8-64-8A

NT140WHM-N14 Product Specification

33 OF 35

Address (HEX)	Function	Hex	Dec	crc	Input values.	Notes
23	Established timing 1	00	0	-	-	-
24	Established timing 2	00	0	-	-	-
25	Established timing 3	00	0	-	-	-
26	Standard timing #1	01	1	-	-	Not Used
27		01	1	-	-	
28	Standard timing #2	01	1	-	-	Not Used
29		01	1	-	-	
2A	Standard timing #3	01	1	-	-	Not Used
2B		01	1	-	-	
2C	Standard timing #4	01	1	-	-	Not Used
2D		01	1	-	-	
2E	Standard timing #5	01	1	-	-	Not Used
2F		01	1	-	-	
30	Standard timing #6	01	1	-	-	Not Used
31		01	1	-	-	
32	Standard timing #7	01	1	-	-	Not Used
33		01	1	-	-	
34	Standard timing #8	01	1	-	-	Not Used
35		01	1	-	-	
36	Detailed timing monitor or descriptor #1	3E	62	-	72.3	72.3MHz Main clock
37		1C	28	-	-	-
38		56	86	-	1366	Hor Active = 1366
39		A0	160	-	160	Hor Blanking = 160
3A		50	80	-	-	4 bits of Hor. Active + 4 bits of Hor. Blanking
3B		00	0	-	768	Ver Active = 768
3C		16	22	-	22	Ver Blanking = 22
3D		30	48	-	-	4 bits of Ver. Active + 4 bits of Ver. Blanking
3E		30	48	-	48	Hor Sync Offset = 48
3F		20	32	-	32	H Sync Pulse Width = 32
40		36	54	-	3	V sync Offset = 3 line
41		00	0	-	6	V Sync Pulse width : 6 line
42		35	53	-	309	Horizontal Image Size = 309 mm (Low 8 bits)
43		AD	173	-	173	Vertical Image Size = 173 mm (Low 8 bits)
44		10	16	-	-	4 bits of Hor Image Size + 4 bits of Ver Image Size
45	00	0	-	0	Hor Border (pixels)	
46	00	0	-	0	Vertical Border (Lines)	
47	1A	26	-	-	Refer to right table	

SPEC. NUMBER
S8-64-8A

SPEC. TITLE
NT140WHM-N14 Product Specification

PAGE
34 OF 35

Address (HEX)	Function	Hex	Dec	crc	Input values.	Notes
48	Detailed timing/monit or descriptor #2	3E	62	-	72.3	72.3MHz Main clock
49		1C	28	-		
4A		56	86	-	1366	Hor Active = 1366
4B		A0	160	-	160	Hor Blanking = 160
4C		50	80	-	-	4 bits of Hor. Active + 4 bits of Hor. Blanking
4D		00	0	-	768	Ver Active = 768
4E		16	22	-	22	Ver Blanking = 22
4F		30	48	-	-	4 bits of Ver. Active + 4 bits of Ver. Blanking
50		30	48	-	48	Hor Sync Offset = 48
51		20	32	-	32	Hor Sync Pulse Width = 32
52		36	54	-	3	V sync Offset = 3 line
53		00	0	-	6	V Sync Pulse width : 6 line
54		35	53	-	309	Horizontal Image Size = 309 mm (Low 8 bits)
55		AD	173	-	173	Vertical Image Size = 173 mm (Low 8 bits)
56		10	16	-	-	4 bits of Hor Image Size + 4 bits of Ver Image Size
57		00	0	-	0	Hor Border (pixels)
58	00	0	-	0	Vertical Border (Lines)	
59	1A	26	-	-	Refer to right table	
5A	00	0	-	-	ASCII Data Sting Tag	
5B	00	0	-	-		
5C	00	0	-	-		
5D	FE	254	-	-		
5E	00	0	-	-	Manufacture name :BOEDT	
5F	42	66	-	B		
60	4F	79	-	O		
61	4	69	-	E		
62	20	32	-	-		
63	44	68	-	D		
64	54	84	-	T		
65	0A	10	-	-		
66	20	32	-	-		
67	20	32	-	-		
68	20	32	-	-		
69	20	32	-	-		
6A	20	32	-	-		
6B	20	32	-	-		

Address (HEX)	Function	Hex	Dec	crc	Input values.	Notes
6C	Detailed timing/monit or descriptor #4	00	0	-	-	Product Name Tag (ASCII) Model name : NT140WHM-N14
6D		00	0	-	-	
6E		00	0	-	-	
6F		FE	254	-	-	
70		00	0	-	-	
71		4E	78	-	N	
72		54	84	-	T	
73		31	49	-	1	
74		34	52	-	4	
75		30	48	-	0	
76		57	87	-	W	
77		48	72	-	H	
78		4D	77	-	M	
79		2D	45	-	-	
7A		4E	78	-	N	
7B		31	49	-	1	
7C	34	52	-	4		
7D	0A	10	-	-		
7E	Extension flag	00	0	-	-	
7F	Checksum	EC	236	236	-	