



PROPRIETARY NOTE

THIS SPECIFICATION IS THE PROPERTY OF BOE AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF BOE AND MUST BE RETURNED TO BOE UPON ITS REQUEST

TITLE : NV140FHM-N4N

Customer: DELL

Product Specification

Rev. P0

(DELL DPN :WCDHX)

BOE Optoelectronics Technology Co., Ltd

SPEC. NUMBER

S8-65-8C-257

PRODUCT GROUP

TFT-LCD

Rev.

P0

ISSUE DATE

2020.02.16

PAGE

1 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev. P0

2020.02.16

REVISION HISTORY

(√) Preliminary Specification

() Final Specification

Revision No.	Page	Description of Changes	Date	Prepared
P0	32	Initial Release	2.16	Zi Lei

REVIEWED**Designer****Manager**

Pu Xun(Array)

Wang Xiaoyuan

Pan Ruiqi(Sell)

Li Zhe

Peng Yuanfong(CF)

Li Min

Chen Yao(EF)

Xu Bo

Ge ShiKang(MO)

Li Yucheng

Huang Longbo(QE)

Huang Yuan

Zhao Yanli(PI)

Chen Gang

APPROVED

Zi Lei(PM)

SPEC. NUMBER

SPEC. TITLE

PAGE

S8-65-8C-257

NV140FHM-N4N Product Specification Rev. P0

2 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Contents

No.	Items	Page
1.0	General Description	4
2.0	Absolute Maximum Ratings	6
3.0	Electrical Specifications	7
4.0	Optical Specifications	11
5.0	Interface Connection	15
6.0	Signal Timing Specification	16
7.0	Input Signals, Display Colors & Gray Scale of Colors	20
8.0	Power Sequence	26
9.0	Connector Description	27
10.0	Mechanical Characteristics	28
11.0	Reliability Test	29
12.0	Handling & Cautions	30
13.0	Label	31
14.0	Packing Information	33
15.0	Mechanical Outline Dimension	34
16.0	EDID Table	36
17.0	General Precautions	40
18.0	Appendix	42

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

3 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

1.0 GENERAL DESCRIPTION

1.1 Introduction

NV140FHM-N4N is a color active matrix TFT LCD module using amorphous silicon TFT's (Thin Film Transistors) as an active switching devices. This module has a 14.0inch diagonally measured active area with Full-HD resolutions (1920 horizontal by 1080 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical stripe and this module can display 6bit colors and color gamut 45%. The TFT-LCD panel used for this module is a low reflection and higher color type. Therefore, this module is suitable for Notebook PC. The LED driver for back-light driving is built in this model.

All input signals are eDP1.2 interface compatible.




Figure 1. Drive Architecture

1.2 Features

- 2 lane eDP interface with 2.1Gbps link rates
- Thin and light weight
- 6bit color depth, color gamut 45%
- Single LED lighting bar (Bottom side/Horizontal Direction)
- Data enable signal mode
- Side mounting frame
- Green product (RoHS & Halogen free product)
- On board LED driving circuit
- Low driving voltage and low power consumption
- On board EDID chip
- DPCD Version 1.1
- Function : SDRRS/CABC/BIST

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

4 OF 63



PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

1.3 Application

- Notebook PC (Wide type)

1.4 General Specification

The followings are general specifications at the model NV140FHM-N4N. (listed in Table 1)

<Table 1. General Specifications>

Parameter	Specification	Unit	Remarks
Active area	309.312 (H) × 173.988 (V)	mm	
Number of pixels	1920 (H) × 1080 (V)	pixels	
Pixel pitch	161.1(H) × 161.1(V)	um	
Pixel arrangement	RGB Vertical stripe		
Display colors	6bit		
Color gamut	45%		
Display mode	Normally Black		
Dimensional outline	315.812 ± 0.3(H) × 186.088 ± 0.3 + 1.6 (max) for FPC (V) × 2.55 ± 0.15 (W/O PCB) & 5.25(max) (W/ PCB) (T)	mm	
Weight	300(Max.)	g	
Surface treatment	Fine AG		
Surface hardness	3H		
Back-light	Bottom edge side, 1-LED lighting bar type		Note 1
Power consumption	P _D : 0.7(Max)	W	@Mosaic
	P _{BL} : 2.4(Max)	W	
	P _{Total} : 3.1(Max)	W	@Mosaic

Notes : 1. LED Lighting Bar (36*LED Array)

SPEC. NUMBER
S8-65-8C-257

SPEC. TITLE
NV140FHM-N4N Product Specification Rev. P0

PAGE
5 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

2.0 ABSOLUTE MAXIMUM RATINGS

The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.

< Table 2. Absolute Maximum Ratings >

Ta=25+/-2°C

Parameter	Symbol	Min.	Max.	Unit	Remarks
Power Supply Voltage	V _{DD}	-0.3	4.0	V	Note 1
eDP input Voltage	V _{eDP}	0	2.0	V	
Logic Supply Voltage	V _{IN}	V _{SS} -0.3	V _{DD} +0.3	V	
Operating Temperature	T _{OP}	0	+50	°C	Note 2
Storage Temperature	T _{ST}	-20	+60	°C	

Notes :

1. Permanent damage to the device may occur if maximum values are exceeded functional operation should be restricted to the condition described under normal operating conditions.

2. Temperature and relative humidity range are shown in the figure below.

95 % RH Max. (40 °C ≥ Ta) Maximum wet-bulb temperature at 39°C or less.(Ta >40°C)No condensation.




Figure 2. Temperature and Relative Humidity Range

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

6 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

3.0 ELECTRICAL SPECIFICATIONS**3.1 Electrical Specifications**

< Table 3. Electrical Specifications >

Ta=25+/-2°C

Parameter		Min.	Typ.	Max.	Unit	Remarks
Power Supply Voltage	V _{DD}	3.0	3.3	3.6	V	Note 1
Permissible Input Ripple Voltage	V _{RF}	-10% VDD	-	+10% VDD	V	Note 4
CABC Control Level	High Level	2	-	3.6	V	@V _{DDIO} =2.5 V Note 5
	Low Level	0	-	0.3	V	
BIST Control Level	High Level	2	-	3.6	V	
	Low Level	0	-	0.3	V	
Power Supply Inrush Current	Inrush	-	-	2	A	Note3
Power Supply Current	Mosaic	I _{DD}	-	212	mA	
	Red	I _{DD}	-	303	mA	
	Green	I _{DD}	-	303	mA	
	Blue	I _{DD}	-	303	mA	
Power Consumption	Mosaic	P _M	-	0.7	W	
	Red	P _R	-	1.0	W	
	Green	P _G	-	1.0	W	
	Blue	P _B	-	1.0	W	
	BLU	P _{BL}	-	2.4	W	Note 2
	Total	P _{Total}	-	3.1	W	Note 1

SPEC. NUMBER
S8-65-8C-257SPEC. TITLE
NV140FHM-N4N Product Specification Rev. P0PAGE
7 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

3.0 ELECTRICAL SPECIFICATIONS

3.1 Electrical Specifications

Notes :

- The supply voltage is measured and specified at the interface connector of LCM.

The current draw and power consumption specified is for 3.3V at 25 °C.(Typ. value for reference)

- Mosaic pattern 8*8
- R/G/B patterns



(a)



(b)



Figure 3. Power Measure Patterns

- Calculated value for reference ($V_{LED} \times I_{LED}$)

- Measure condition (Figure 4)

- Input voltage range:3.0~3.6V.Test condition: Oscilloscope bandwidth 20MHz, AC coupling

- CABC&BIST setting

Pin No	Define	Enable	Disable
1	CABC	Pull High	Pull Low/Floating
14	BIST	Pull High	Pull Low/Floating




Figure 4. Inrush Measure Condition

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

8 OF 63

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev.P0	2020.02.16

3.2 Backlight Unit

< Table 4. LED Driving Guideline Specifications >

Ta=25+/-2°C

Parameter		Min.	Typ.	Max.	Unit	Remarks
LED Forward Voltage	V _F	-	-	2.9	V	
LED Forward Current	I _F	-	19.4	-	mA	
LED Power Input Voltage	V _{LED}	5	12	21	V	
LED Power Input Current	I _{LED}	-	-	200	mA	Note 1
LED Power Consumption	P _{LED}	-	-	2.15	W	
Power Supply Voltage for LED Driver Inrush	I _{LED} inrush	-	-	1.5	A	
LED Life-Time	N/A	1,000	-	-	Hour	I _F = 19.5mA Note 2
EN Control Level	Backlight On	2	-	3.6	V	Note 4
	Backlight Off	0	-	0.3	V	
PWM Control Level	High Level	2	-	3.6	V	
	Low Level	0	-	0.3	V	
PWM Control Frequency	F _{PWM}	200	-	2,000	Hz	
Duty Ratio		5	-	100	%	Note 3

Notes :

1. The current and power consumption with LED Driver are under the V_{LED} = 12.0V , 25°C, PWM Duty 100% .
2. The LED life-time defines the estimated time to 50% degradation of initial luminous.
3. Measure condition (Figure 5).
- 4.LED_EN&PWM setting

Pin No	Define	Enable	Disable
22	LED_EN	Pull High	Pull Low/Floating
23	PWM	Pull High	Pull Low/Floating




Figure 5. Inrush Measure Condition

SPEC. NUMBER S8-65-8C-257	SPEC. TITLE NV140FHM-N4N Product Specification Rev. P0	PAGE 9 OF 63
------------------------------	---	-----------------

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16


3.3 LED Structure

Figure 6. LED Structure

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

10 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

4.0 OPTICAL SPECIFICATION

4.1 Overview

The test of optical specifications shall be measured in a dark room (ambient luminance ≤ 1 lux and temperature = $25 \pm 2^\circ\text{C}$) with the equipment of luminance meter system (PR730&PR810) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of θ and Φ equal to 0° . We refer to $\theta=0$ ($=03$) as the 3 o'clock direction (the "right"), $\theta=90$ ($=012$) as the 12 o'clock direction ("upward"), $\theta=180$ ($=09$) as the 9 o'clock direction ("left") and $\theta=270$ ($=06$) as the 6 o'clock direction ("bottom"). While scanning θ and/or Φ , the center of the measuring spot on the display surface shall stay fixed. The backlight should be operating for 30 minutes prior to measurement. VDD shall be $3.3 \pm 0.3\text{V}$ at 25°C . Optimum viewing angle direction is 0'clock.

4.2 Optical Specifications

<Table 5. Optical Specifications>

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark
Viewing Angle Range	Horizontal	Θ_3	$CR \geq 10$	80	85	-	Deg.	Note 1
		Θ_9		80	85	-	Deg.	
	Vertical	Θ_{12}		80	85	-	Deg.	
		Θ_6		80	85	-	Deg.	
Luminance Contrast Ratio		CR	$\Theta = 0^\circ$	600	800	-		Note 2
Luminance of White	5 Points	L_w	$\Theta = 0^\circ$ LED = 19.4mA	212	250	-	cd/m ²	Note 3
White Luminance Uniformity	5 Points	ΔY_5		80%	-	-		Note 4
	13 Points	ΔY_{13}		65%	-	-		
White Chromaticity		W_x	$\Theta = 0^\circ$	0.283	0.313	0.343		Note 5
		W_y		0.299	0.329	0.359		
Reproduction of Color	Red	R_x	$\Theta = 0^\circ$	Typ.-0.03	0.585	Typ.+0.03		
		R_y			0.365			
	Green	G_x			0.351			
		G_y			0.581			
	Blue	B_x			0.164			
		B_y			0.132			
Color Gamut				Min	45	-	%	NTSC
Response Time (Rising + Falling)		T _{RT}	Ta= 25°C $\Theta = 0^\circ$	-	16	25	ms	Note 6
Cross Talk		CT	$\Theta = 0^\circ$	-	-	2.0	%	Note 7

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

11 OF 63

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev.P0	2020.02.16

Notes :

1. Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing angles are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface (see Figure 7).
2. Contrast measurements shall be made at viewing angle of $\Theta = 0$ and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state. (see Figure 7) Luminance Contrast Ratio (CR) is defined mathematically.

$$CR = \frac{\text{Luminance when displaying a white raster}}{\text{Luminance when displaying a black raster}}$$

3. Center Luminance of white is defined as luminance values of 5 point average across the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in Figure 8 for a total of the measurements per display.
4. The White luminance uniformity on LCD surface is then expressed as : $\Delta Y = \text{Minimum Luminance of 5(or 13) points} / \text{Maximum Luminance of 5(or 13) points}$. (see Figure 8 and Figure 9).
5. The color chromaticity coordinates specified in Table 5 shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.
6. The electro-optical response time measurements shall be made as Figure 10 by switching the "data" input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is T_r , and 90% to 10% is T_f .
7. Cross-Talk of one area of the LCD surface by another shall be measured by comparing the luminance (Y_A) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (Y_B) of that same area when any adjacent area is driven dark. (See Figure 11).

SPEC. NUMBER	SPEC. TITLE	PAGE
S8-65-8C-257	NV140FHM-N4N Product Specification Rev. P0	12 OF 63

BOE

PRODUCT GROUP

REV


ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

4.3 Optical Measurements



Optical characteristics measurement setup

Figure 7. Measurement Set Up




Figure 8. White Luminance and Uniformity Measurement Locations (5 points)

Center Luminance of white is defined as luminance values of center 5 points across the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in Figure 7 for a total of the measurements per display.

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

13 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16




Figure 9. Uniformity Measurement Locations (13 points)

The White luminance uniformity on LCD surface is then expressed as: ΔY_5 = Minimum Luminance of five points / Maximum Luminance of five points (see Figure 8), ΔY_{13} = Minimum Luminance of 13 points / Maximum Luminance of 13 points (see Figure 9).




Figure 10. Response Time Testing

The electro-optical response time measurements shall be made as shown in Figure 10 by switching the “data” input signal ON and OFF. Tr: The luminance to change from 10% to 90% ,Tf: The luminance to change from 90% to 10% .

The test system : LMS PR810

SPEC. NUMBER
S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

14 OF 63

BOE

PRODUCT GROUP


REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16



$$\text{Cross Talk (\%)} = \left| \frac{Y_B - Y_A}{Y_A} \right| \times 100$$

Figure 11. Cross Talk Modulation Test Description

Where:

 Y_A = Initial luminance of measured area (cd/m²) Y_B = Subsequent luminance of measured area (cd/m²)

The location 1/2/3/4 measured will be exactly the same in both patterns. The test background gray is from L64 to L192. Take the largest data as the result.

Cross Talk of one area of the LCD surface by another shall be measured by comparing the luminance (Y_A) of a 25mm diameter area, with all display pixels set to a gray level, to the luminance (Y_B) of that same area when any adjacent area is driven dark. (Refer to Figure 11)

The test system: PR730




Figure 12. Brightness and Gray-scale Contrast

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

15 OF 63



PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

5.0 INTERFACE CONNECTION

5.1 Electrical Interface Connection

The electronics interface connector is **UJU IS050-L30B-C10**.

The connector interface pin assignments are listed in Table 6.

<Table 6. Pin Assignments for the Interface Connector>

Pin No.	Symbol	Description
1	CABC_EN	CABC_Function Reserved
2	H_GND	Ground
3	LANE1_N	eDP RX Channel 1 Negative
4	LANE1_P	eDP RX Channel 1 Positive
5	H_GND	Ground
6	LANE0_N	eDP RX Channel 0 Negative
7	LANE0_P	eDP RX Channel 0 Positive
8	H_GND	Ground
9	AUX_CH_P	eDP AUX CH Positive
10	AUX_CH_N	eDP AUX CH Negative
11	H_GND	Ground
12	LCD_VCC	Power Supply, 3.3V (typ.)
13	LCD_VCC	Power Supply, 3.3V (typ.)
14	BIST	Panel Self Test Enable
15	H_GND	Ground
16	H_GND	Ground
17	HPD	Hot Plug Detect Output
18	BL_GND	LED Ground
19	BL_GND	LED Ground
20	BL_GND	LED Ground
21	BL_GND	LED Ground
22	BL_ENABLE	LED Enable Pin(+3.3V Input)
23	BL_PWM	System PWM Signal Input
24	NC	No Connection
25	NC	No Connection
26	BL_POWER	LED Power Supply 5V-21V
27	BL_POWER	LED Power Supply 5V-21V
28	BL_POWER	LED Power Supply 5V-21V
29	BL_POWER	LED Power Supply 5V-21V
30	NC	No Connection

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

16 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16


5.2 eDP Interface

Figure 13. eDP Interface Architecture

Note:

Transmitter : Parade DP501 or equivalent.

Transmitter is not contained in module.

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

17 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16


5.3 Data Input Format

Figure 14. Display Position of Input Data (V-H)

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

18 OF 63

DAS-RD-20190067-0

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

5.4 Back-light & LCM Interface Connection

BLU Interface Connector: DEREN BOE-120521-01.

<Table 7. Pin Assignments for the BLU Connector>

Pin No.	Symbol	Description	Pin No.	Symbol	Description
1	LED	LED cathode connection	6	GND	Ground Connection
2	LED	LED cathode connection	7	NC	No Connection
3	LED	LED cathode connection	8	Vout	LED anode connection
4	LED	LED cathode connection	9	Vout	LED anode connection
5	NC	No Connection	10	Vout	LED anode connection

SPEC. NUMBER
S8-65-8C-257SPEC. TITLE
NV140FHM-N4N Product Specification Rev. P0PAGE
19 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

6.0 SIGNAL TIMING SPECIFICATION**6.1 The NV140FHM-N4N Is Operated By The DE Only**

< Table 8. Signal Timing Specification >

Item		Symbols	Min	Typ	Max	Unit
Clock	Frequency	1/Tc	146.8	147.8	148.8	MHz
Frame Period		Tv	1115	1120	1125	lines
			-	60	-	Hz
			-	16.67	-	ms
Vertical Display Period		Tvd	-	1080	-	lines
One line Scanning Period		Th	2195	2200	2205	clocks
Horizontal Display Period		Thd	-	1920	-	clocks

Note : The above is as optimized setting.

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

20 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

6.2 eDP Rx Interface Timing Parameter

The specification of the eDP Rx interface timing parameter is shown in Table 9.

<Table 9. eDP Main-Link RX TP4 Package Pin Parameters>

Item	Symbol	Min	Typ	Max	Unit	Remark
Spread spectrum clock (Link clock down-spreading)	SSC	0	-	0.5	%	
Differential peak-to-peak input voltage at package pins	$V_{RX-DIFFp-p}$	100	-	320	mV	
Rx input DC common mode voltage	$V_{RX_DC_CM}$	0	-	2	V	
Differential termination resistance	$R_{RX-DIFF}$	80	-	120	Ω	
Single-ended termination resistance	R_{RX-SE}	40	-	60	Ω	
Rx short circuit current limit	I_{RX_SHORT}	-	-	20	mA	
Intra-pair skew at Rx package pins (HBR) RX intra-pair skew tolerance at HBR	$L_{RX_SKW_INTR_PAIR}$	-	-	60	ps	
AC Coupling Capacitor	C_{SOURCE_ML}	75	-	200	nF	Source side




Figure 15. Main link differential pair

SPEC. NUMBER
S8-65-8C-257

SPEC. TITLE
NV140FHM-N4N Product Specification Rev. P0

PAGE
21 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16




Figure 16. VRX-DIFFp-p & LRX_SKEW_INTRA_PAIR

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

22 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

<Table 10. HPD Characteristics>

Item	Symbol	Min	Typ	Max	Unit	Remark
HPD voltage	V _{HPD}	2.25	-	3.6	V	Sink side
Hot Plug Detection Threshold	-	2.0	-	-	V	Source side
Hot Unplug Detection Threshold	-	-	-	0.8	V	
HPD_IRQ Pulse Width	HPD_IRQ	0.5	-	1	ms	
HPD_TimeOut	-	2.0	-	-	ms	




Figure 17. HPD Events

SPEC. NUMBER
S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE
23 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

<Table 11. AUX Characteristics>

Item	Symbol	Min	Typ	Max	Unit	Remark
AUX unit interval	U_{IAUX}	0.4	0.5	0.6	Us	
AUX peak-to-peak input differential voltage	$V_{AUX-RX-DIFFp-p}$	0.29	-	1.38	V	Sink Side Connector Pin
AUX CH termination DC resistance	$R_{AUX-TERM}$	80	100	120	Ohm	
AUX DC common mode voltage	$V_{AUX-DC-CM}$	0	-	2	V	
AUX turn around common mode voltage	$V_{AUX-TURN-CM}$			0.3	V	
AUX short circuit current limit	$I_{AUX-SHORT}$	-	-	90	mA	
AUX AC Coupling Capacitor	$C_{SOURCE-AUX}$	75	-	200	nF	Source side




Figure 18. AUX differential pair

SPEC. NUMBER
S8-65-8C-257SPEC. TITLE
NV140FHM-N4N Product Specification Rev. P0PAGE
24 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

7.0 INPUT SIGNALS, BASIC DISPLAY COLORS & GRAY SCALE OF COLORS

<Table 12. Input Signal & Basic Display Colors & Gray Scale of Colors >

	Colors & Gray scale	Data signal																	
		R0	R1	R2	R3	R4	R5	G0	G1	G2	G3	G4	G5	B0	B1	B2	B3	B4	B5
Basic colors	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
	Light Blue	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Purple	1	1	1	1	1	1	0	0	0	0	0	0	1	1	1	1	1	1
	Yellow	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0	0	0	0
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Gray scale of Red	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Darker	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	↑						↑						↑					
	▽	↓						↓						↓					
	Brighter	1	0	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	▽	0	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
	Red	1	1	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0
Gray scale of Green	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0
	Darker	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0
	△	↑						↑						↑					
	▽	↓						↓						↓					
	Brighter	0	0	0	0	0	0	1	0	1	1	1	1	0	0	0	0	0	0
	▽	0	0	0	0	0	0	0	1	1	1	1	1	0	0	0	0	0	0
	Green	0	0	0	0	0	0	1	1	1	1	1	1	0	0	0	0	0	0
Gray scale of Blue	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0
	Darker	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0
	△	↑						↓						↑					
	▽	↓						↓						↓					
	Brighter	0	0	0	0	0	0	0	0	0	0	0	0	1	0	1	1	1	1
	▽	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1
	Blue	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1
Gray scale of White & Black	Black	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	△	1	0	0	0	0	0	1	0	0	0	0	0	1	0	0	0	0	0
	Darker	0	1	0	0	0	0	0	1	0	0	0	0	0	1	0	0	0	0
	△	↑						↑						↑					
	▽	↓						↓						↓					
	Brighter	1	0	1	1	1	1	1	0	1	1	1	1	1	0	1	1	1	1
	▽	0	1	1	1	1	1	0	1	1	1	1	1	0	1	1	1	1	1
	White	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

25 OF 63

DAS-RD-2019006-0

A4(210 X 297)

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev.P0	2020.02.16

8.0 POWER SEQUENCE

To prevent a latch-up or DC operation of the LCD module, the power on/off sequence shall be as shown in below.




Figure 19. Power Sequence

- $0.5\text{ms} \leq T1 \leq 10\text{ms}$
- $0\text{ms} < T2 \leq 200\text{ns}$
- $0\text{ms} < T3 \leq 200\text{ms}$
- $T4+T5+T6+T8 > 80\text{ms}$
- $0\text{ms} < T7 \leq 50\text{ms}$
- $50\text{ms} < T8$
- $0\text{ms} < T9$
- $100\text{ms} < T10 < 500\text{ms}$
- $0.5\text{ms} \leq T11 \leq 10\text{ms}$
- $500\text{ms} \leq T12$
- $0\text{ms} < T13$
- $0\text{ms} < T14$
- $0\text{ms} < T15$
- $0\text{ms} < T16$
- $0.5\text{ms} \leq T17$
- $0.5\text{ms} \leq T18$

Notes:

1. When the power supply VDD is 0V, keep the level of input signals on the low or keep high impedance.
2. Do not keep the interface signal high impedance when power is on. Back Light must be turn on after power for logic and interface signal are valid.

SPEC. NUMBER	SPEC. TITLE	PAGE
S8-65-8C-257	NV140FHM-N4N Product Specification Rev. P0	26 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

9.0 Connector Description

Physical interface is described as for the connector on LCM.

These connectors are capable of accommodating the following signals and will be following components.

9.1 TFT LCD Module

< Table 13. Signal Connector >

Connector Name /Description	For Signal Connector
Manufacturer	IPEX or Compatible
Type/ Part Number	IPEX 20455-030E or Compatible
Mating Housing/ Part Number	MSAK24025P30 or Compatible





Figure 20. RC Loading Test Schematic Diagram



Item	RC Loading	
WCDHX	R	C
	17.0Kohm	35.8uF

Figure 21. VCC Loop R/C Loading Parameter

SPEC. NUMBER
S8-65-8C-257

SPEC. TITLE
NV140FHM-N4N Product Specification Rev. P0

PAGE
27 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

10.0 MECHANICAL CHARACTERISTICS

10.1 Dimensional Requirements

Figure 26 shows mechanical outlines for the model NV140FHM-N4N.
Other parameters are shown in Table 14.

<Table 14. Dimensional Parameters>

Parameter	Specification	Unit
Active Area	309.312 (H) × 173.988 (V)	mm
Number of pixels	1920 (H) X 1080 (V) (1 pixel = R + G + B dots)	pixels
Pixel pitch	161.1(H) × 161.1(V)	um
Pixel arrangement	RGB Vertical stripe	
Display colors	6bit	
Display mode	Normally Black	
Dimensional outline	315.812 ± 0.2 (H) × 186.038 ± 0.3 +1.6 (max) for FPC (V) × 2.85 ± 0.15 (W/O PCB) & 5.25(max) (W/ PCB) (T)	mm
Weight	300(Max.)	g

10.2 Mounting

See Figure 26.

10.3 Anti-Glare and Polarizer Hardness.

The surface of the LCD has an Anti-Glare coating to minimize reflection and a coating to reduce scratching. The polarizer hardness is 3H.

10.4 Light Leakage

There shall not be visible light from the back-lighting system around the edges of the screen as seen from a distance 50cm from the screen with an overhead light level of 350lux.

SPEC. NUMBER
S8-65-8C-257

SPEC. TITLE
NV140FHM-N4N Product Specification Rev. P0

PAGE
28 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

11.0 RELIABILITY TEST

The reliability test items and its conditions are shown in below.

<Table 15. Reliability Test>

No	Test Items	Conditions	Remark
1	High temperature storage test	Ta = 60°C , 60%RH, 240 hrs	
2	Low temperature storage test	Ta = -20°C , 240 hrs	
3	High temperature & high humidity operation test	Ta = 50°C , 80%RH, 240 hrs	
4	High temperature operation test	Ta = 50°C , 60%RH, 240 hrs	
5	Low temperature operation test	Ta = 0°C , 240 hrs	
6	Thermal shock	Ta = -20°C ↔ 60°C (0.5 hr), 60% ± 3%RH, 100 cycle	
7	Vibration test (non-operating)	Ta = 25°C , 60%RH 1.5G, 10~500Hz, Sine X,Y,Z / Sweep rate : 1 hour	Note 1
8	Shock test (non-operating)	Ta = 25°C , 60%RH, 220G, Half Sine Wave 2msec ± X, ± Y, ± Z Once for each direction	Note 1
9	Electro-static discharge test (operating)	Air : 150 pF, 330Ω, ± 15 KV Contact : 150 pF, 330Ω, ± 8 KV Ta = 25°C , 60%RH,	Note 2

Notes :

1. The fixture must be hard enough , so that the module would not be twisted or bent.
2. Self- recovery and restart recovery is allowed. No hardware failures.

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

29 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

12.0 HANDLING & CAUTIONS**(1) Cautions when taking out the module**

- Pick the pouch only, when taking out module from a shipping package.

(2) Cautions for handling the module

- As the electrostatic discharges may break the LCD module, handle the LCD module with care. Peel a protection sheet off from the LCD panel surface as slowly as possible.
- As the LCD panel and back - light element are made from fragile glass material, impulse and pressure to the LCD module should be avoided.
- As the surface of the polarizer is very soft and easily scratched, use a soft dry cloth without chemicals for cleaning.
- Do not pull the interface connector in or out while the LCD module is operating.
- Put the module display side down on a flat horizontal plane.
- Handle connectors and cables with care.

(3) Cautions for the operation

- When the module is operating, do not lose CLK, ENAB signals. If any one of these signals is lost, the LCD panel would be damaged.
- Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.

(4) Cautions for the atmosphere

- Dew drop atmosphere should be avoided.
- Do not store and/or operate the LCD module in a high temperature and/or humidity atmosphere. Storage in an electro-conductive polymer packing pouch and under relatively low temperature atmosphere is recommended.

(5) Cautions for the module characteristics

- Do not apply fixed pattern data signal to the LCD module at product aging.
- Applying fixed pattern for a long time may cause image sticking.

(6) Other cautions

- Do not disassemble and/or re-assemble LCD module.
- Do not re-adjust variable resistor or switch etc.
- When returning the module for repair or etc. Please pack the module not to be broken. We recommend to use the original shipping packages.

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

30 OF 63

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev.P0	2020.02.16

13.0 LABEL

(1) Product Label




Figure 22. Product Label

Module ID Naming Rule:

<Table 16. Module ID Naming Rule>

Digit Code	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
Code	B	9	A	F	1	7	8	8	D	3	1	0	0	0	0	6	8
Description	Product Name		Product Grade	B8	Year	Month	Model Extension Code (Last 4 Digits of FG CODE)					Serial No. 00001-ZZZZZZ					

SPEC. NUMBER
S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE
31 OF 63

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev.P0	2020.02.16

(2) High voltage caution label




Figure 23. High Voltage Caution Label

(3) Box label




Figure 24. Box Label

Serial number marked part needs to print, show as follows:

1. FG-CODE (Before 12 bit)
2. Product quantity
3. Box ID
4. Date
5. The client section material number (The client)
6. FG-Code After four
7. The supplier code
8. Total Size: 100 × 50mm

<Table 17. Box Label Naming Rule >

Digit Code	1	2	3	4	5	6	7	8	9	10	11	12	13
Code	B	9	A	F	1	7	8	N	0	0	3	2	7
Description	Product Name		Product Grade	B8	Year		Month	Revision	BOX Serial Number				

SPEC. NUMBER S8-65-8C-257	SPEC. TITLE NV140FHM-N4N Product Specification Rev. P0	PAGE 32 OF 63
------------------------------	---	------------------

BOE

PRODUCT GROUP

REV

ISSUE DATE


Customer Spec

Rev.P0

2020.02.16

14.0 PACKING INFORMATION

14.1 Packing Order



- Put 1 pcs spacer in tray and 1 pcs MDL on spacer.
3pcs MDL/Tray, 4pcs Spacer/Tray.
- Put 7 pcs tray and 1 pcs tray cover in PE bag.
- Put PE bag with 2EPE cover in the inner box.
- 21pcs MDL/Box, 18Box/Pallet, 378pcs MDL/Pallet.

Figure 25. Packing Order

14.2 Note

- Box dimension: 480mm*350mm*285mm
- Package quantity in one box: 21pcs
- Total weight: 10.6kg/Box

SPEC. NUMBER
S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE
33 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

15.0 MECHANICAL OUTLINE DIMENSION

Figure 26. TFT-LCD Module Outline Dimension (Front View)

NOTES:

1. WARPAGE AND DEFORMATION SPEC: 0.5mm MAX.
 2. THE eDP CONNECTOR IS MEASURED AT PIN 1 AND MATING LINE
 3. UNSPECIFIED TOLERANCE REFER TO 0.3 mm
 4. THE MEASUREMENT METHOD FOR THE DIMENSION OF MODULE, PLEASE REFRE TO REMARK A
 5. TOP POLARIZER IS THE HIGHEST PORTION.
 6. "()" MEANS REFERENCE DIMENSIONS.
 7. CRITICAL DIMENSION: ① ~ ⑩
- CPK: ① ~ ③




Figure 24. Highest Point Position

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

34 OF 63

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev.P0	2020.02.16



Figure 28. TFT-LCD Module Outline Dimensions (Rear view)

NOTES:

1. WARPAGE AND DEFORMATION SPEC : 0.5mm MAX.
2. THE eDP CONNECTOR IS MEASURED AT PIN 1 AND MATING LINE
3. UNSPECIFIED TOLERANCE REFER TO ± 0.3 mm
4. THE MEASUREMENT METHOD FOR THE DIMENSION OF MODULE, PLEASE REFRE TO REMARK A
5. TOP POLARIZER IS THE HIGHEST PORTION.
6. "()" MEANS REFERENCE DIMENSIONS.
7. CRITICAL DIMENSION: ① ~ ⑬
CPK: ① ~ ③

SPEC. NUMBER S8-65-8C-257	SPEC. TITLE NV140FHM-N4N Product Specification Rev. P0	PAGE 35 OF 63
------------------------------	---	------------------

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

16.0 EDID Table

Address (HEX)	Function	Hex	Dec	Input values	Notes
00	Header	00	0	0	EDID Header
01		FF	255	255	
02		FF	255	255	
03		FF	255	255	
04		FF	255	255	
05		FF	255	255	
06		FF	255	255	
07		00	0	0	
08	ID Manufacturer Name	09	9	BOE	ID = BOE
09		E5	229		
0A	ID Product Code	1D	29	2333	ID = 2333
0B		09	9		
0C	32-bit serial No.	00	0	0	
0D		00	0	0	
0E		00	0	0	
0F		00	0	0	
10	Week of manufacture	0D	13	13	
11	Year of Manufacture	1E	30	2020	Manufactured in 2020
12	EDID Structure Ver.	01	1	1	EDID Ver 1.0
13	EDID revision #	04	4	4	EDID Rev. 0.4
14	Video input definition	95	149	-	Video Signal Interface
15	Max H image size	1F	31	31	31cm (Approx)
16	Max V image size	11	17	17	17cm (Approx)
17	Display Gamma	78	20	2.2	Gamma curve = 2.2
18	Feature support	03	3	-	Feature Support
19	Red/Green low bits	EF	239	-	Red / Green Low Bits
1A	Blue/White low bits	35	53	-	Blue / White Low Bits
1B	Red x high bits	55	149	0.585	Red (x) = 10010101 (0.585)
1C	Red y high bits	5D	93	0.365	Red (y) = 01011101 (0.365)
1D	Green x high bits	59	89	0.351	Green (x) = 01011001 (0.351)
1E	Green y high bits	94	148	0.581	Green (y) = 10010100 (0.581)
1F	Blue x high bits	2A	42	0.164	Blue (x) = 00101010 (0.164)
20	Blue y high bits	21	33	0.132	Blue (y) = 00100001 (0.132)
21	White x high bits	50	80	0.313	White (x) = 01010000 (0.313)
22	White y high bits	54	84	0.329	White (y) = 01010100 (0.329)
23	Established timing 1	00	0	-	--
24	Established timing 2	00	0	-	
25	Established timing 3	00	0	-	

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

36 OF 63

DAS-RD-2019006-0

A4(210 X 297)

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

26	Standard timing #1	01	1		Not Used
27		01	1		
28	Standard timing #2	01	1		Not Used
29		01	1		
2A	Standard timing #3	01	1		Not Used
2B		01	1		
2C	Standard timing #4	01	1		Not Used
2D		01	1		
2E	Standard timing #5	01	1		Not Used
2F		01	1		
30	Standard timing #6	01	1		Not Used
31		01	1		
32	Standard timing #7	01	1		Not Used
33		01	1		
34	Standard timing #8	01	1		Not Used
35		01	1		
36	Detailed timing/monitor descriptor #1	C0	192	147.84	147.84MHz Main clock
37		39	57		
38		80	128	1920	Hor Active = 1920
39		15	24	280	Hor Blanking = 280
3A		71	113		4 bits of Hor. Active + 4 bits of Hor. Blanking
3B		38	56	1080	Ver Active = 1080
3C		28	40	40	Ver Blanking = 40
3D		40	64	-	4 bits of Ver. Active + 4 bits of Ver. Blanking
3E		30	48	48	Hor Sync Offset = 48
3F		20	32	32	H Sync Pulse Width = 32
40		36	54	3	V sync Offset = 3 line
41		00	0	6	V Sync Pulse width : 6 line
42		35	53	309	Horizontal Image Size = 309 mm (Low 8 bits)
43		AE	174	174	Vertical Image Size = 174 mm (Low 8 bits)
44		10	16	-	4 bits of Hor Image Size + 4 bits of Ver Image Size
45		00	0	0	Hor Border (pixels)
46		00	0	0	Vertical Border (Lines)
47		1A	26	-	Detailed timing Definition

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

37 OF 63

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev.P0	2020.02.16

48	Detailed timing/monitor descriptor #2	34	52	118.27	118.27199999999999MHz Main clock
49		2E	46		
4A		80	128	1920	Hor Active = 1920
4B		18	24	280	Hor Blanking = 280
4C		71	113	-	4 bits of Hor. Active + 4 bits of Hor. Blanking
4D		38	56	1080	Ver Active = 1080
4E		28	40	40	Ver Blanking = 40
4F		40	64	-	4 bits of Ver. Active + 4 bits of Ver. Blanking
50		30	48	48	Hor Sync Offset = 48
51		20	32	32	H Sync Pulse Width = 32
52		36	54	3	V sync Offset = 3 line
53		00	0	6	V Sync Pulse width = 6 line
54		35	53	309	Horizontal Image Size = mm (Low 8 bits)
55		AE	174	174	Vertical Image Size = mm (Low 8 bits)
56		10	16	-	4 bits of Hor Image Size + 4 bits of Ver Image Size
57		00	0	0	Hor Border (pixels)
58		00	0	0	Vertical Border (Lines)
59		1A	26	-	Detailed timing Definition
5A	Detailed timing/monitor descriptor #3	00	0	0	ASCII Data Sting Tag
5B		00	0	0	
5C		00	0	0	
5D		FE	254	0	
5E		00	0	0	Dell P/N:WCDHX
5F		57	87	W	
60		43	67	C	
61		44	68	D	
62		49	72	H	
63		50	88	X	
64		00	0	00000000	EDID:X00
65		4E	78	N	BOE PN
66		56	86	V	
67		31	49	1	
68		34	52	4	
69		4E	78	N	
6A		34	52	4	
6B		4E	78	N	

SPEC. NUMBER S8-65-8C-257	SPEC. TITLE NV140FHM-N4N Product Specification Rev. P0	PAGE 38 OF 63
------------------------------	---	------------------

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

6C	Detailed timing/monitor descriptor #4	00	0		Flag
6D		00	0		
6E		00	0		
6F		00	0		Data Type Tag: Manufacturer Specified Data 00
70		00	0		Flag
71		00	0	-	Color Depth : 6bit +2 bit FRC : No Supports
72		41	65	-	Lamps of LED Light Bars : one Configuration : single light bar Panel Illumination : WLED
73		21	33	-	Intel sDRRs : Supports Intel DRIS : No Supports Max. Frame Rate : 65Hz Min. Frame Rate : 40Hz
74		99	153	-	Digital PWM : PWM only Maximum Typical Luminance : 250
75		00	0	-	Pixel Structure : RGB v-strip Transflective : no AG/Glossy : Anti-Glare
76		10	16		Dynamic Backlight Control : DBC type 1 Color Management : NTSC
77		00	0		Active Gamma Control : no support(default) Motion Blur : no support(default)
78		00	0	-	In-Cell Scanner : no support(default) Wireless Enhancement Hardware : no support(default)
79		01	10	-	In-Cell Touch : no support(default) Interface : eDP Overdrive : no support(default) Interface Channels : two
7A		01	1	-	3-D Hardware Support : no support(default) Electronic Privacy : no electronic privacy hardware control BIST Hardware support : support(default)
7B		0A	10		Format: terminate with ASCII code 0Ah and pad field with ASCII code 20h
7C		20	32		
7D		20	32		
7E	Extension flag	00	0	1	0 : 1个EDID; N-1: N个EDID
7F	Checksum	F8	248	-	Checksum

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

39 OF 63

DAS-RD-2019006-0

A4(210 X 297)

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

17.0 GENERAL PRECAUTIONS

17.1 HANDLING

(1) When the module is assembled, It should be attached to the system firmly using every mounting holes.

Be careful not to twist or bend the modules.

(2) Refrain from strong mechanical shock or any force to the module. Otherwise, it may cause improper operation or damage to the module.

(3) Note that polarizers are very fragile and could be easily damaged. Do not press or scratch the surface harder than 1 HB pencil lead.

(4) Wipe off water droplets or oil immediately. If you leave the droplets for a long time, Staining and discoloration may occur.

(5) If the surface of the polarizer is dirty, clean it using some absorbent cotton or soft cloth.

(6) The desirable cleaners are water, IPA (Isopropyl Alcohol) or Hexane. Do not use Ketone type materials(ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanently damage to the polarizer due to chemical reaction.

(7) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contact with hands, legs or clothes, it must be washed away thoroughly with soap.

(8) Protect the module from static, it may cause damage to the module.

(9) Use fingerstalls with soft gloves to keep display clean during the incoming inspection and assembly process.

(10) Do not disassemble the module.

(11) Do not pull or fold the LED FPC.

(12) Do not touch any component which is located on the back side.

(13) Protection film for polarizer on the module shall be slowly peeled off just before use so that the electrostatic charge can be minimized.

(14) Pins of connector shall not be touched directly with bare hands.

17.2 STORAGE

(1) Do not leave the module in high temperature, and high humidity for a long time. It is highly recommended to store the module with temperature from 0 to 35 °C and relative humidity of less than 70%.

(2) Do not store the TFT-LCD module in direct sunlight.

(3) The module shall be stored in a dark place. It is prohibited to apply sunlight or fluorescent light during the store.

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

40 OF 63

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev.P0	2020.02.16

17.3 OPERATION

- (1) Do not connect, disconnect the module in the “ Power On” condition.
- (2) Power supply should always be turned on/off by following item 8.0 “ Power on/off sequence “.
- (3) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.
- (4) The standard limited warranty is only applicable when the module is used for general Notebook applications. If used for purposes other than as specified, BOE is not to be held reliable for the defective operations. It is strongly recommended to contact BOE to find out fitness for a particular purpose.

17.4 OTHERS

- (1) Avoid condensation of water. It may result in improper operation or disconnection of electrode.
- (2) Do not exceed the absolute maximum rating value. (the supply voltage variation, input voltage variation, Variation in part contents and environmental temperature, so on) Otherwise the module may be damaged.
- (3) If the module displays the same pattern continuously for a long period of time, it can be the situation when The “ image sticks” to the screen.
- (4) This module has its circuitry PCB's on the rear or bottom side and should be handled carefully to avoid being stressed.

SPEC. NUMBER S8-65-8C-257	SPEC. TITLE NV140FHM-N4N Product Specification Rev. P0	PAGE 41 OF 63
------------------------------	---	------------------

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev.P0	2020.02.16

Appendix A

The Measurement Methods for the Dimensions of Module

1. Caliper:

Thickness of Outline (Without/With PCB)

2. Coordinate Measuring Machine:

- Length of Outline (Without Tape Wrinkle or Bulged)
- Width of Outline (Without PCB) (Without Tape Wrinkle or Bulged)
- Width of Outline (With PCB)
- CF Polarizer Size
- Active Area (Or AA_BM) Size
- Active Area to Outline (Without Tape Wrinkle or Bulged)
- Active Area to CF Polarizer
- The Distance of Bracket Holes
- P-Cover to Outline (Without Tape Wrinkle or Bulged)
- Length of P-Cover
- Connector Pin 1 to Outline (Without Tape Wrinkle or Bulged)

3. Height Gauge: The Different Height of Root and Top on the Bracket
(Need to Calculate From Bracket Angle Spec.)

4. Feeler Gauge: The Warpage Spec. of Module

Notes:

Except the Critical Dimensions as Above, Other Dimensions are Measured by Coordinate Measuring Machine If Necessary.

SPEC. NUMBER S8-65-8C-257	SPEC. TITLE NV140FHM-N4N Product Specification Rev. P0	PAGE 42 OF 63
------------------------------	---	------------------

BOE

PRODUCT GROUP

REV




ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix B

LCM to A-Cover / sponges z-gap

	Plastic Cover (LCM Thickness: Max)	Metal Cover (LCM Thickness: Max)
A	>0mm	>0mm
B	Min: 1.0mm	Min: 0.8mm
Without the open area of back cover		

Purpose

The reflector area is very sensitive, we suggest that design enough z-gap to decrease the risk of water ripple, white spot and other abnormal display

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

43 OF 63

BOE

PRODUCT GROUP

REV


ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix B

LCM to A-Cover / sponges z-gap**Purpose**

If attach sponges or rubbers which correspond to white reflector area, it may cause white spot, pooling or other relate issues. We suggest that attach wide range sponges / rubbers which can cover the LCM back-bezel opening

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

44 OF 63

BOE

PRODUCT GROUP

REV


ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix B

LCM to side wall / protrusions

	Normal border	Narrow border
D1/D2	Min: 0.45mm	Min: 0.35mm
C1	Min: 0.50mm	
C2	Min: 0.50mm	
E1/E2	Min: 0.55mm	

Purpose

We suggest that design enough gap around LCM to prevent shock test failure, or interference, cell crack, abnormal display...etc. in the reliability test

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

45 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix B

LCM to B-cover z-gap

B-cover Tape	Gap
Without	0.15 ~ 0.25mm
With	0.15 ~ 0.20mm

Purpose

Too less z-gap between system B-cover and LCM top pol has high risk to cause cell crack, pooling, light leakage and other issues

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

46 OF 63

BOE

PRODUCT GROUP

REV


ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix B

B-cover tape to top pol edge

If attach b-cover and LCM with tapes,
Please let tapes to be located out of top pol edges 0.4mm away on 4 sides

Purpose

To avoid the B-cover tape override top pol and cause pooling or light leakage issue

SPEC. NUMBER
S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

47 OF 63

BOE

PRODUCT GROUP

REV


ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix B

Antenna Cable & Webcam wire

If sponge within the reflector area is necessary, we suggest that the gap between reflector and sponge is more than 0.5mm

Purpose

1. We suggest that do not set Antenna or WebCam cable / wire go behind LCM to avoid backpack test, hinge test, twist test or pogo test with abnormal display
2. If the cable / wire is necessary to go behind LCM, please make a groove with rounds or chamfers to protect the cable / wire, or attach with higher sponge / rubbers adjacent to the cable / wire route
3. Suggest that attach the cable / wire with tapes to A-cover
4. Do not attach anything with LCM reflector area. If attach cable / wire with LCM reflector area, it may cause pooling, white spot, light leakage and other related issues

SPEC. NUMBER
S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

48 OF 63

BOE

PRODUCT GROUP

REV


ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix B

LCM paste area

Attachment area

Purpose

If use the stretch remove tapes to fix LCM with A-cover, please set the stretch remove tapes correspond to the LCM back-bezel and do not let the tapes override the back-bezel's level step of opening

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

49 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE



Customer Spec

Rev.P0

2020.02.16

Appendix B

LCM pressable area



Purpose

1. LCM is fixed on A-cover by double-sided tap which can stick LCM after using the press jig stress LCM during assembling.
2. To avoid panel broken the design of pressure head of press jig can not only pin on cell panel. The pressure head needs to pin on the LCM frame, which the LCM frame can share the pressure of the pressing head.

SPEC. NUMBER
S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

50 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix B

Wire setting

Purpose

Wire should be placed between Protrusions and A-cover. If place the wire between LCM and Protrusions, it may interfere with LCM when assembling B-covers, or even cause LCM breakage in reliability test.

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

51 OF 63

BOE

PRODUCT GROUP

REV




ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix B

A-cover strength**Purpose**


1. It is recommended that Rib height is higher than LCM, in order to avoiding press on LCM edge panels.
2. As for LCM is more stronger than Rib, the L Bracket is be recommended.

SPEC. NUMBER
S8-65-8C-257SPEC. TITLE
NV140FHM-N4N Product Specification Rev. P0PAGE
52 OF 63

BOE	PRODUCT GROUP	REV	ISSUE DATE
	Customer Spec	Rev.P0	2020.02.16

Appendix B

System A-cover Inner Surface



Purpose

There should not exist any burr, segment gap or protrusions beside Logo, which would cause White Spot or Glass Broken by stress concentration.

SPEC. NUMBER
S8-65-8C-257

SPEC. TITLE
NV140FHM-N4N Product Specification Rev. P0

PAGE
53 OF 63

BOE

PRODUCT GROUP

REV



ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix B

Keyboard area & Mouse pad

F max 0.3mm

Purpose

In order to avoiding LCM fragments in reliability test, the step surface of Keyboard and Mouse pad transmits smoothly, and should not be right-angle. For example, when Pogo testing if the broken hole is done in this location, it is easy to produce fragments.

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

54 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE



Customer Spec

Rev.P0

2020.02.16

Appendix B

System cover reliability



Purpose

The permanent deformation part of System cover after the reliability test, including sponge and other structures or components, can not touch LCM.

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

55 OF 63

BOE

PRODUCT GROUP

REV


ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix B

A/B-cover near LCD PCBA

No magnetic object

Purpose

There should not have magnet object near LCM PCBA, which is prone to cause physical or electricity noise issue

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

56 OF 63

BOE

PRODUCT GROUP

REV

ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix B

A-cover add sponges on Boss side wall**Purpose**

We suggest to attach Sponges to the side of the Boss column of A-cover to reduce the panel broken possibility in assembly. It is recommended to this design synchronously.

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

57 OF 63

BOE

PRODUCT GROUP

REV


ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix B

LCM to A-Cover / sponges z-gap**Purpose**

Bent product: The position of system connector and FPC should be staggered in X direction. Otherwise, when testing, the system Cable line extrudes FPC, leading to FPC Crack. (Panel FPC Bonding location is related to Mask and can not be changed easily)

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

58 OF 63

BOE

PRODUCT GROUP

REV


ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix C

HPD Signal recognition

Purpose

When HPD glitch of source device minimum is 2.0(V).

SPEC. NUMBER
S8-65-8C-257SPEC. TITLE
NV140FHM-N4N Product Specification Rev. P0PAGE
59 OF 63

BOE

PRODUCT GROUP

REV


ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix C

HPD Signal Definition IRQ (Interrupt Request)**Purpose**

When HPD signal low than 0.5ms to 1ms, the source device should check sink status field from the DPCE and take link training again.

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

60 OF 63

BOE

PRODUCT GROUP

REV



ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix C

Main link eye diagram of TP3

Measured TP3 on LCM connector.

Downstream Device Mask at TP3

	UI	Voltage
1	0.246	0
2	0.5	0.075
3	0.755	0
4	0.5	-0.075

Eye for TP3 at HBR

	UI	Voltage
1	0.375	0
2	0.5	0.023
3	0.625	0
4	0.5	-0.023

Eye for TP3 at RBR

Purpose

1. Main Link EYE Diagram should meet TP3 point of VESA.
2. The measure method is through access fixture.

SPEC. NUMBER
S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE
61 OF 63



PRODUCT GROUP

REV

ISSUE DATE


Customer Spec

Rev.P0

2020.02.16

Appendix C

Impedance Profile through a DP Connector



Differential Impedance Profile Measurement Data Example

Segment	Differential Impedance Value	Maximum Tolerance
Fixture	100Ω/85Ω VESA	±10%
Connector	100Ω/85Ω VESA	±10%
Wire management	100Ω/85Ω VESA	±10%
Cable	100Ω/85Ω VESA	±5%

Impedance Profile Values for Cable Assembly

Purpose

Cable Impedance Profile 100ohm for Cable Assembly

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

62 OF 63

BOE

PRODUCT GROUP

REV


ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix C

Main Link Pixel Freq information value of MSA data

Purpose

1. It need to fix pixel freq information value of MSA data output to prevent the initial abnormal pixel freq information value from incoming after power on.
2. BOE can read DPCD to check this value. Ex: BIOS is 1.62G , but into windows is 2.7G.

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

63 OF 63

BOE

PRODUCT GROUP

REV


ISSUE DATE

Customer Spec

Rev.P0

2020.02.16

Appendix C

Main Link Pixel Freq information value of MSA data

Example:

Freq	Cycle Time	PWM Rising Time	PWM Falling Time
200Hz	5ms	$\leq 1\mu s$	$\leq 1\mu s$
1KHz	1ms	$\leq 200ns$	$\leq 200ns$

Purpose

1. LED driver need to calculate the duty cycle of input PWM signal.
2. To avoid backlight flicker visible on LCD, system input PWM suggest :
PWM rising $\leq 200\text{ppm} \times \text{cycle time}$; PWM falling $\leq 200\text{ppm} \times \text{cycle time}$.

SPEC. NUMBER

S8-65-8C-257

SPEC. TITLE

NV140FHM-N4N Product Specification Rev. P0

PAGE

64 OF 63